Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 199

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | | |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type | GU10 | | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No | | | |
| Colour-tuneable light source: | No | Envelope: | - | | | |
| High luminance light source: | No | | | | | |
| Anti-glare shield: | No | Dimmable: | Yes | | | |
| Product parameters | | | | | | |

| Product parameters | | | | | | |
|---|---|----------------------------|---|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consump mode (kWh/1000 up to the nearest | 0 h), rounded | 7 | Energy efficiency class | G | | |
| Useful luminous indicating if it ref in a sphere (360 cone (120 ^o) or in (90 ^o) | fers to the flux D ^o), in a wide | 450 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 | | |
| On-mode po expressed in W | ower (P _{on}), | 7,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked stand for CLS, express rounded to the se | ed in W and | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer | Height | 55 | Spectral power | See image | | |
| | Width | 50 | distribution in the | in last page | | |
| without | Depth | 50 | - | | | |
| I | - | 1 | 1 | Page 1 / | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|--|----------------|--|--|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 55 | | | |
| | | Chromaticity coordinates (x and y) | 0,390 0,390 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 16 | Survival factor | - | | | |
| the lumen maintenance factor | 0,98 | | | | | |
| Parameters for LED and OLED mains light sources: | | | | | | |
| displacement factor (cos φ1) | 0,90 | Colour consistency in McAdam ellipses | 3 | | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W) | - | | | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,9 | | | |

(a)'-' : not applicable;

(b)'_-' : not applicable;

