Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources			2013 With regard to ener	87
Supplier's name	or trade mark:	V-TAC		
Supplier's addre	ess: V-TAC Europ	e Ltd, bul. Rozhen 4	11, Sofia, Bulgaria	
Model identifier	r: 2041			
Type of light sou	ırce:			
Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		DC Female connector		
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable	light source:	No	Envelope:	-
High luminance light source:		No		
Anti-glare shield	:	No	Dimmable:	No
		Product para	imeters	
Parameter		Value	Parameter	Value
		General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	E
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	4	Spectral power	See image
dimensions	Width	8	distribution in the	in last page
without	Depth	500		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,380			
		coordinates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

