# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

# Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

### Model identifier: 2592

# Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

#### **Product parameters** Value Parameter Value Parameter General product parameters: 7 Energy consumption in on-Energy efficiency G mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (duse), 140 in 1000...10000 Correlated colour indicating if it refers to the flux Sphere (360°) temperature, in a sphere (360°), in a wide rounded to the cone (120º) or in a narrow cone nearest 100 Κ, (90º) or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set 7,0 On-mode (P<sub>on</sub>), Standby power (P<sub>sb</sub>), 0,00 power expressed expressed in W in W and rounded to the second decimal Networked standby power (P<sub>net</sub>) Colour rendering 56 \_ index, rounded to for CLS, expressed in W and rounded to the second decimal the nearest integer, or the range of CRI-

			values that can be set			
OuterHeightdimensionsWidthwithoutDepthseparatecontrol gear,lightingcontrol partsandnon-lightingcontrol parts,ifany(millimetre)	Height	4	Spectral power distribution in the	See image in last page		
	Width	10				
	1 000	range 250 nm to 800 nm, at full-Ioad				
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-		
			Chromaticity	0,203		
			coordinates (x and y)	0,238		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		-100	Survival factor	1,00		
the lumen maintenance factor		0,96				
(a)		<u>L</u>	l			

(a)'-' : not applicable;

(b)'-' : not applicable;

