Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 4062

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | DLS | | | |
|-------------------------------|-------|---------------------------------|-----|--|--|--|
| Light source cap-type | AR111 | | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | | |
| Colour-tuneable light source: | No | Envelope: | - | | | |
| High luminance light source: | No | | | | | |
| Anti-glare shield: | No | Dimmable: | No | | | |
| Product parameters | | | | | | |

| Parameter | | Value | Parameter | Value | | |
|--|-----------------------------------|-----------------------------|---|--------------|--|--|
| General product parameters: | | | | | | |
| Energy consum mode (kWh/100 up to the neares | D0 h), rounded | 15 | Energy efficiency class | G | | |
| Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º) | efers to the flux 50°), in a wide | 780 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 | | |
| On-mode p expressed in W | ower (P _{on}), | 15,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked stand for CLS, expres rounded to the s | sed in W and | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer | Height | 111 | Spectral power | See image | | |
| dimensions | Width | 63 | distribution in the | in last page | | |
| without | Depth | 63 | 1 | Page 1 / 3 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|-------|--|----------------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordinates (x and y) | 0,377 0,375 | | | |
| Parameters for directional light sources: | | | | | | |
| Peak luminous intensity (cd) | 8 171 | Beam angle in degrees, or the range of beam angles that can be set | 20 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 55 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,96 | | | | | |

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

